

WEARABLE

8675i Wearable Scanner

The 8675i offers always at-hand wearable scanning to improve workflow productivity. Premium scanning performance including FlexRange™ option enables wearable efficiency. Small, lightweight and ergonomic, the 8675i will help your workers perform.

Overview

The 8675i is designed for superior performance providing always-at-hand scanning to enhance workflow productivity. With premium scanning capabilities, it processes even damaged or low-quality barcodes swiftly.

Wearable Efficiency:

Ergonomically optimized, the 8675i minimizes height off the finger to avoid interference in workspaces. All user-contact surfaces are designed for comfort, allowing easy adjustments and simple use. The triggered ring can be easily swapped for left or right-hand configurations, while the low-profile finger strap buckle prevents finger interference. Users can convert from ring to glove to lanyard/belt clip options seamlessly and without tools, and accessories accommodate a comprehensive size range.

FlexRange™ Scanning:

FlexRange Scanning technology allows users to scan from near contact to 5 feet for 100% UPC and up to 10 meters (33 feet) for 100 mil Code 39 barcodes, enabling wearable efficiency in a wider range of applications. Standard range configurations offer high speed scanning at a lower cost for workflows where extended range is not required.

Designed for Demanding Workflows:

The 8675i supports multi-shift operations with a replaceable battery for extended service life. Rated for 2,000 tumbles and equipped with IP65 sealing for durability in harsh environments, this device also features a new outdoor aimer for precise targeting in bright sunlight, ensuring optimal performance in various conditions. User-facing LEDs indicate Bluetooth status, battery charge, and health.

Specifications

FEATURES

For Use With

• 8675i chargers and accessories

Features

• Triggered ring or glove form factors

Connectivity

Bluetooth

DIMENSIONS

Overall Dimensions

• 65.2mm x 30.3mm x 15.2mm (2.6 in x 1.2 in x 0.6 in)

SCANNING SPECIFICATIONS

Scan Distance

- Mid Range (0-5m)
- Standard Range (0-1m)

NETWORK

Bluetooth Specifications

• 5.1

HARDWARE

Battery Type

Li-ion Battery

Charging

Contact Charging

ENVIRONMENTAL

Storage Temperature Range

• -20C to 60C (-4F to 140F)

Operating Humidity

• 0 to 95% relative humidity (non-condensing)

STANDARDS & APPROVALS

Protection Ratings

• IP65

IP Rating

• IP65

Drop Specifications

• 1.8m Mil-Std-810; 50x1.5m (5') drop to concrete across operating temperatures

SERVICE TERMS

Warranty Duration

• Two years (battery one year)

OTHERS

Industry

- Aerospace
- Logistics & Warehouses
- Manufacturing
- Retail



Please sign in to view part numbers available for purchase based on your account

Sign In

Q Search

Part Number	46-00332-R
Description	RPL, ALIGNED OPTICSBENCH, FUSION
	SIGN IN
Part Number	50131491-001
Description	POWER CORD, 1.5M, 10A INDIA
	SIGN IN
Part Number	8675I200SR-2-R
Description	WEARABLE SR LANYARD SCANNER WBATT
	SIGN IN
Part Number	8675I300FR-2-A
Description	WEARABLE FR GLOVE SCANNER WBATT, ASIA
	SIGN IN
Part Number	8675I300FR-2-N
Description	WEARABLE FR GLOVE SCANNER WBATT, NA
	SIGN IN
.	007F1000FD 0 D
Part Number	8675I300FR-2-R
Description	WEARABLE FR GLOVE SCANNER WBATT, ROW
	SIGN IN
Dart Number	967E1200CD 2 A

Description	WEARABLE SR GLOVE SCANNER WBATT, ASIA
	SIGN IN
Part Number	8675I300SR-2-J
Description	WEARABLE SR GLOVE SCANNER WBATT, JAPAN
	SIGN IN
Part Number	8675I300SR-2-N
Description	WEARABLE SR GLOVE SCANNER WBATT, NA
	SIGN IN
Part Number	8675I300SR-2-R
Description	WEARABLE SR GLOVE SCANNER WBATT, ROW
	SIGN IN
Rows 10 ¥	<u>Previous</u> <u>1</u> <u>2</u> <u>3</u> <u>4</u> <u>5</u> <u>6</u> <u>Next</u>

Product Number



Please sign in to view part numbers available for purchase based on your account

Sign In

46-00332-R

RPL,ALIGNED OPTICSBENCH,FUSION

46-00332-R

RPL,ALIGNED OPTICSBENCH,FUSION

50131491-001

POWER CORD, 1.5M, 10A INDIA

50131491-001

POWER CORD, 1.5M, 10A INDIA

8675I200SR-2-R

WEARABLE SR LANYARD SCANNER WBATT

8675I200SR-2-R

WEARABLE SR LANYARD SCANNER WBATT

8675I300FR-2-A

WEARABLE FR GLOVE SCANNER WBATT, ASIA

8675I300FR-2-A

WEARABLE FR GLOVE SCANNER WBATT, ASIA

8675I300FR-2-N

WEARABLE FR GLOVE SCANNER WBATT, NA

8675I300FR-2-N

WEARABLE FR GLOVE SCANNER WBATT, NA

8675I300FR-2-R

WEARABLE FR GLOVE SCANNER WBATT, ROW

8675I300FR-2-R

WEARABLE FR GLOVE SCANNER WBATT, ROW

8675I300SR-2-A

WEARABLE SR GLOVE SCANNER WBATT, ASIA

8675I300SR-2-A

WEARABLE SR GLOVE SCANNER WBATT, ASIA

8675I300SR-2-J

WEARABLE SR GLOVE SCANNER WBATT, JAPAN

8675I300SR-2-J

WEARABLE SR GLOVE SCANNER WBATT, JAPAN

8675I300SR-2-N

WEARABLE SR GLOVE SCANNER WBATT, NA

8675I300SR-2-N

WEARABLE SR GLOVE SCANNER WBATT, NA

8675I300SR-2-R

WEARABLE SR GLOVE SCANNER WBATT, ROW

8675I300SR-2-R

WEARABLE SR GLOVE SCANNER WBATT, ROW




8675i Wearable Ring Scanner



Discover the Ultra-rugged, Compact 8675i Wearable Scanner

Complete Your Solution



Maximize the value of your scanners with complete support throughout the full lifecycle.



Honeywell Industrial Automation 855 S Mint St Charlotte, NC 28202 800-582-4263

Product name

© Current year Honeywell International Inc. All rights reserved.



 $This \ document \ was \ generated \ on \ (YYYY-MM-DD, HH:mm:ss). \ Subject \ to \ change \ without \ notice.$